







GINGER

CASUAL
GRIP

Gaston MILLE®

| | | | |
|--|-------|--|---|
|  | 35/48 |  ALUMINIUM 200J |  TEXTILE 1430N |
|  IEC EN 61340-5-1 | S3 |  POROMAX® |  1.052KG |





INDUSTRY / FINISHING CONSTRUCTION / LOGISTICS



HIGHLIGHTS Very comfortable fitting

SAFETY LEVEL STANDARDS

S3 SRA ESD
EN ISO 20345:2011

-  Safety toe-cap (resistant up to 200J)
-  Penetration-resistant midsole (resistant up to 1 430N)
-  Antislip sole
-  Antistatic footwear
-  Energy absorption in the heel region
-  Fuel Oil resistant outsole
-  Water resistant upper
-  Large fit
-  Electro Static Discharge
-  High performance grip SRA*

COMPOSITION

| | |
|-------------------------------|---|
| Upper | Washable microfiber - antibacterial treatment Very resistant and repellent |
| Lining | Poromax® - polyamid textile bringing softness, flexibility & anti-abrasiveness. Breathability with anti-bacterial treatment |
| Toe-cap | Aluminium - thin & light : comfortable |
| Footbeds | Mille Soft® - Removable + antibacterial |
| Penetration Resistant midsole | Textile |
| Sole | PU/PU |
| Net weight/pair (size 43) | 1 052g |
| Sizes | 35-48 / F5-13 |
| Item code | GBN03 |

MADE IN FRANCE

* SRA: Slipping resistance on ceramic tile wet with soap solution

** SRB: Slipping resistance on smooth steel with glycerol

MILLE SAS • 69 Rue Marcel Valérien - 84350 Courthézon - France • Tel. +33(0) 4 90 70 40 40 • Email: welcome@gastonmille.fr • www.gastonmille.com

The product specifications & performances are guaranteed only if Gaston Mille footbeds are worn. MILLE SAS may modify the specifications of the product manufacture.